

2009 - 2012 Indian Motorcycle Service Manual

Chief Classic • Chief Dark Horse • Chief Bomber Chief Roadmaster • Chief Vintage • Chief Blackhawk Dark



2009-2012 Indian Motorcycle PN 9923695



2009-2012

INDIAN MOTORCYCLE

CHIEF CLASSIC • CHIEF DARK HORSE • CHIEF BOMBER
CHIEF ROADMASTER • CHIEF VINTAGE • CHIEF BLACKHAWK DARK

FOREWORD

The information printed within this publication includes the latest product information at the time of print. The most recent version of this Service Manual is available to Indian Dealers in electronic format at www.polarisdealers.com.

This manual is designed primarily for use by trained Indian service technicians in a properly equipped shop and should be kept available for reference in the shop area. All references to left and right side of the vehicle are from the operator's perspective when seated in a normal riding position.

Some procedures outlined in this manual require a sound knowledge of mechanical theory, tool use, and shop procedures in order to perform the work safely and correctly. Read the text and be familiar with the service procedures before starting the work. Certain procedures will require the use of special tools. Use only the proper tools as specified. If you have any doubt as to your ability to perform any of the procedures outlined in this service manual, contact an authorized Indian dealer for service.

Comments or suggestions about this manual should be submitted via Ask Polaris. Consumers can direct comments or suggestions to: Service Publications Department, Polaris Sales Inc., 2100 Hwy 55, Medina, Minnesota 55340.

Publication Printed November 2011 (PN 9923695)

© Copyright 2011 Polaris Sales Inc. All information contained within this publication is based on the latest product information at the time of publication. Due to constant improvements in the design and quality of production components, some minor discrepancies may result between the actual vehicle and the information presented in this publication. Depictions and/or procedures in this publication are intended for reference use only. No liability can be accepted for omissions or inaccuracies. Any reprinting or reuse of the depictions and/or procedures contained within, whether whole or in part, is expressly prohibited. Printed in U.S.A.

TRADEMARKS

The following are Common Law or Registered Trademarks of Polaris Industries Inc.:

CHIEF™

CHIEF CLASSIC[™]

CHIEF DARK HORSE™

CHIEF BOMBER™

CHIEF ROADMASTER®

CHIEF VINTAGE®

CHIEF BLACKHAWK[™]

BLACKHAWK DARK®

POWERPLUS®

Polaris Industries Inc. acknowledges the following products mentioned in this manual:

Loctite, Registered Trademark of the Henkel Corporation

Nyogel, Registered Trademark of Wm. F. Nye Co.

FLEXLOC, Registered Trademark of SPS Technologies

Fluke, Registered Trademark of John Fluke Mfg. Co.

Mity-Vac, Registered Trademark of Neward Enterprises, Inc.

STA-BIL, Registered Trademark of Gold Eagle

Torx, Registered Trademark of Textron

Michelin, Registered Trademark of Michelin North America, Inc.

Metzeler, Registered Trademark of Pirelli Tyre, S.P.A.

GENERAL & MAINTENANCE	SPECIFICATIONS / GAUGES	1
	MAINTENANCE	2
	FRAME / BODY / EXHAUST	3
ENGINE	LUBRICATION & COOLING	4
	FUEL SYSTEM / FUEL INJECTION	5
	ENGINE REMOVAL & INSTALLATION	6
	CYLINDER HEAD & VALVES	7
	CYLINDER & PISTON	8
	CLUTCH, PRIMARY, & SHIFT	9
	TRANSMISSION & CRANKSHAFT	10
	DRIVE LINE	11
CHASSIS	FRONT WHEEL & SUSPENSION	12
	REAR WHEEL & SUSPENSION	13
	TIRES	14
	BRAKES	15
ELECTRICAL	CHARGING SYSTEM & BATTERY	16
	IGNITION SYSTEM	17
	ELECTRIC STARTER	18
	LIGHTING & INSTRUMENTATION	19

CHAPTER 1 SPECIFICATIONS / GAUGES

GENERAL INFORMATION				1.2
TRADEMARKS	1	.2		
SERVICE RULES				
SAFETY INFORMATION				1.3
UNDERSTANDING SAFETY LABELS & INSTRUCTIONS				
GENERAL SPECIFICATIONS				1.4
2009 INDIAN CHIEF.				
2009 INDIAN CHIEF				
GENERAL SPECIFICATIONS				16
2010 INDIAN CHIEF			• • •	1.0
2010 INDIAN CHIEF				
GENERAL SPECIFICATIONS				10
			• • •	1.0
2011 INDIAN CHIEF				
GENERAL SPECIFICATIONS			٠.	1. 10
2012 INDIAN CHIEF				
2012 INDIAN CHIEF				
VEHICLE LOADING			• • •	1.12
GROSS VEHICLE WEIGHT RATING (GVWR)				
VEHICLE INFORMATION			• • •	1.13
VEHICLE IDENTIFICATION NUMBER (VIN) 2009-2011	. 1.1	13		
MODEL NUMBER 2009-2011	. 1.1	13		
VEHICLE IDENTIFICATION NUMBER (VIN) 2012				
MODEL NUMBER 2012				
VIN NUMBER LOCATION				
MANUFACTURER LABEL				
TIRE INFORMATION LABEL				
ENGINE NUMBER LOCATION	1,1	15		
KEY IDENTIFICATION NUMBER				
PUBLICATIONS & TECHNICAL LITERATURE				1,16
PUBLICATION PART NUMBERS				
REFINISHING				1.16
2009-2012 CHIEF PAINT COLORS BY MODEL				
2009-2012 CHIEF PAINT COLOR CODES				
PAINT COLOR CARE - MATTE FINISH (SMOKE)				
BREAK IN PERIOD				1.18
BREAK-IN PROCEDURE	. 1.1	18		
EMISSIONS			*	1.19
INSTRUMENTS	- 2015			1.20
INSTRUMENTATION / CONTROLS				
SPECIAL SERVICE TOOLS				
REFERENCE	• • •			1.26
SAE TAP DRILL SIZES				
METRIC TAP DRILL SIZES				
DECIMAL EQUIVALENTS				
FAHRENHEIT TO CELSIUS.				
MEASUREMENT CONVERSION CHART	· 1.2	41		



SPECIFICATIONS / GAUGES

GENERAL INFORMATION

TRADEMARKS

The following are Common Law or REGISTERED trademarks of Polaris Industries Inc.:

INDIAN MOTORCYCLE; INDIAN; CHIEF; BOMBER; CLASSIC; DARK HORSE; ROADMASTER; VINTAGE BLACKHAWK; BLACKHAWK DARK; POLARIS; POLARIS THE WAY OUT.

Polaris acknowledges the following products mentioned in this manual:

LOCTITE, is a registered trademark of the Henkel Corporation

DUNLOP, is a registered trademark of the Dunlop Tire Corporation.

STA-BIL, is a registered trademark of Gold Eagle

NYOGEL, trademark of Gold Eagle

FLUKE, registered trademark of the Fluke Corporation

XM, a registered trademark of XM® Satellite Radio, Inc.

SERVICE RULES

In order to perform service work efficiently and prevent costly errors, technicians should read the text in this manual and familiarize themselves with the procedures before beginning. Notes, Cautions and Warnings have been included for clarification of text and safety concerns. Knowledge of mechanical theory, tool use and shop procedures are necessary to perform some procedures in this manual safely and correctly.

Use only genuine Indian Motorcycle service parts, including fasteners that require replacement if removed. Do NOT substitute fasteners or hardware.

Cleanliness of parts and tools as well as the work area is of primary importance. Dirt and foreign matter will cause damage to precision parts. Clean the motorcycle before beginning service. Clean all parts before installing.

If difficulty is encountered in removing or installing a component, look to see if a cause for the difficulty can be found. If it is necessary to tap the part into place, use a soft face hammer and tap lightly.

Always follow torque specifications as outlined throughout this manual. Incorrect torquing may lead to serious machine damage or in the case of steering, driveline, and chassis components, can result in loss of control during operation of the motorcycle, which may result in severe personal injury or death.

If a torquing sequence is indicated for nuts, bolts or screws of a certain component, start all fasteners and hand tighten. Following the method and sequence indicated, tighten evenly to the specified torque value. When removing nuts, bolts or screws from a component with several fasteners, loosen them all about 1/4 turn before removing them to prevent distortion of that component.

Replace all oil seals, sealing washers, gaskets, and o-rings with new ones during assembly. Be sure the mating surfaces for the gasket are clean and smooth to avoid leaks and maintain specified tolerances.

Some procedures require removal of retaining rings or clips. Removal can weaken and deform these parts, therefore, they should always be replaced with new parts. When installing new retaining rings and clips, use care not to expand or compress them beyond what is required for installation.

Some service procedures in this manual may call for lubricants and greases have been specially formulated for use with Indian motorcycles. In some applications, warranty coverage may be void if these specially formulated lubricants are not used.

Parts requiring grease should be cleaned thoroughly and fresh grease applied before reassembly. Deteriorating grease loses lubricity and may contain abrasive foreign matter. Always replace locking hardware such as lock nuts or lock washers, fasteners that have pre-applied locking agent, or any other fasteners as noted in this service manual with genuine Indian Motorcycle hardware from an authorized Indian Motorcycle dealer.

Working with batteries can be hazardous. Review all battery warnings and cautions.

